

DH36DPE

Cordless Rotary Hammer Drill

36V

0000000000000

MV
MULTI VOLT
BRUSHLESS



NEW

Top class drilling speed

Easy handling and better operability

Cyclon Dust Extraction Unit with HEPA filter for dust free working

Specifications

		DH36DPE	With dust extractor
Capacity	Concrete	28 mm	20 mm
	Metal	13 mm	
	Wood	32 mm	
Bit shank		SDS-plus	
No load speed	Normal	0 - 950 /min.	
	Low	0 - 700 /min.	
Full load impact rate	Normal	0 - 4,300 /min.	
	Low	0 - 3,170 /min.	
Impact energy		3.2 J	
Motor		Brushless	
Handle shape		Pistol	
Selective operation modes		3	
Drilling holes per charge	Ø 12 x 40 mm	82	
Sound power/sound pressure level		102/91 dB (A)	
Uncertainty K		3 dB (A)	
Vibration total values (triax vector sum) ²	Drilling HD	12.2 m/s ²	10.3 m/s ²
	Uncertainty K	1.5 m/s ²	1.5 m/s ²
Dimensions L x H x W		368 x 276 x 83 mm	510 x 276 x 103 mm
Weight with BSL36A18 ¹		3.6 kg	4.7 kg

Characteristics

- Highest drilling and chipping speed
- Easy handling and better operability due to pistol grip design
- Auto-stop function: timer function allows to drill holes of the same depth with repeat accuracy
- Reactive Force Control: prevents work accidents by shutting the tool off when suddenly twisting
- Soft start control for easy targeting of drilling positions
- Brushless motor for highest efficiency and longest lifespan
- Compact and lightweight for better user comfort
- Cyclon Dust Extraction Unit with HEPA filter for dust free working results
- UVP for reduced vibrations and less fatigue

Standard accessories³

- 2 batteries BSL36A18
- Charger UC18YSL3
- Side handle
- Depth gauge
- Stackable case HSC IV

¹ Weight according to EPTA-Procedure 01/2014.

² Vibration values may vary depending on application and material.

³ Standard accessories vary by country or area.



Cyclon Dust Extraction Unit

376971: in cardboard box
376972: in stackable case HSC II

Read everything about our services at hikoki-powertools.com

HIKOKI
SERVICE

DH36DPE

Cordless Rotary Hammer Drill

36V

0000000000000

NEW
MULTI VOLT
BRUSHLESS



NEW

Top class drilling speed

Easy handling and better operability

Cyclon Dust Extraction Unit with HEPA filter for dust free working

Specifications

		DH36DPE	With dust extractor
Capacity	Concrete	28 mm	20 mm
	Metal	13 mm	
	Wood	32 mm	
Bit shank		SDS-plus	
No load speed	Normal	0 - 950 /min.	
	Low	0 - 700 /min.	
Full load impact rate	Normal	0 - 4,300 /min.	
	Low	0 - 3,170 /min.	
Impact energy		3.2 J	
Motor		Brushless	
Handle shape		Pistol	
Selective operation modes		3	
Drilling holes per charge	Ø 12 x 40 mm	82	
Sound power/sound pressure level		102/91 dB (A)	
Uncertainty K		3 dB (A)	
Vibration total values (triax vector sum) ²	Drilling HD	12.2 m/s ²	10.3 m/s ²
	Uncertainty K	1.5 m/s ²	1.5 m/s ²
Dimensions L x H x W		368 x 276 x 83 mm	510 x 276 x 103 mm
Weight with BSL36A18 ¹		3.6 kg	4.7 kg

Characteristics

- Highest drilling and chipping speed
- Easy handling and better operability due to pistol grip design
- Auto-stop function: timer function allows to drill holes of the same depth with repeat accuracy
- Reactive Force Control: prevents work accidents by shutting the tool off when suddenly twisting
- Soft start control for easy targetting of drilling positions
- Brushless motor for highest efficiency and longest lifespan
- Compact and lightweight for better user comfort
- UVP for reduced vibrations and less fatigue
- Features for dust extraction unit:
 - Cyclone technology for highest dust extraction efficiency
 - Compact design while offering 0,6 liters of dust capacity
 - HEPA filter for superior protection against dust particles

Standard accessories³

- 2 batteries BSL36A18
- Charger UC18YSL3
- Side handle
- Depth gauge
- Stackable case HSC IV
- Cyclon Dust Extraction Unit
- Stackable case HSC II

¹ Weight according to EPTA-Procedure 01/2014.

² Vibration values may vary depending on application and material.

³ Standard accessories vary by country or area.

Read everything
about our services at
hikoki-powertools.com

