

UB18DC

Cordless Construction Light 18V

0000000000000



Dimmable 4,000 Lumen

Long runtime: up to 34 hours

IP65, impact resistant design, and spark protected lens





Specifications		
Voltage		18V
Light source		LED
Brightness	Min. power	700 Lumen
	Max. power	4,000 Lumen
Light color		5,000 K (daylight white)
Colour rendering index		> 80 (natural colour appearance)
Runtime with 5.0 Ah battery ¹	Min. power	21.5 hours
	Max. power	3 hours
Runtime with 8.0 Ah battery ¹	Min. power	34 hours
	Max. power	5 hours
USB power output		5V / 1.0 A
Adjustable angle		126°
IP certification		IP65
Spark protected lens		Yes
Impact resistant		Yes (IK08)
Battery level display		Yes
Dimensions (L x H x W)		270 x 155 x 186 mm
Weight ²		2.1 kg

Characteristics

High Lumen and stepless brightness adjustment for each situation Long runtime: fewer battery changes

Robust, and ready for the toughest construction sites: dust tight, impact resistant, protected against water jets, and sparks

Options for suspending, and fixing the construction light guarantee flexibility in all situations $% \left(1\right) =\left(1\right) \left(1$

Mountable on tripods

USB-port for charging mobile devices, such as smartphones Compatible with all HiKOKI 18V and MULTI VOLT batteries

Read everything about our services at **hikoki-powertools.com**



¹ 5.0 Ah battery: BSL1850 or BSL36A18. 8.0 Ah battery: BSL36B18.

² Weight according to EPTA-Procedure 01/2014.